RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA PULSANTE BLU

Codice prodotto	SNRZB4BA6
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony XB4, blue button head operates with a spring return mechanism. This button head provides an ergonomic interface for controlling your machines. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66 / IP67 / IP69 / IP69K. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB4BA6
Codice produttore	ZB4BA6
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110887495
Classe ETIM	EC000221
Versione ETIM	10
Prezzo pubblico	7.61
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	4
Quantita minima	1
Quantita multipla	1
Quantita cartone	300
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Dust resistant | Impact resistant | Self-earthing | Modular Pushbutton | Screw clamp terminal connection | Spring return | Chromium plated metal bezel | Water resistant | Snap-fit assembly | Flush PushbuttonBlue Pushbutton | Circular Pushbutton | Harmony XB4 | Push-Button | Pushbutton | Push Button
Descrizione breve	Head for non illuminated push button, Harmony XB4, metal, flush, blue, 22mm, spring return, unmarked
Descrizione estesa	This Harmony XB4, blue button head operates with a spring return mechanism. This button head provides an ergonomic interface for controlling your machines. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66 / IP67 / IP69 / IP69K. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	97.65
Codice TARIC	1741
Peso	0.01 kg