RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA PULSANTE GRIGIO

Codice prodotto	SNRZB4BA8
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony XB4, flush greybutton headoperates with a spring return / impulse mechanism. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is clearly distinguishable visually at a distance thanks to clear color. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB4BA8
Codice produttore	ZB4BA8
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110887501
Classe ETIM	EC000221
Versione ETIM	10
Prezzo pubblico	7.62
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	2
Quantita minima	1
Quantita multipla	1
Quantita cartone	150
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	chiave n.520E | modulare | resistente agli urti | estrazione della chiave a sinistra e a destra | nero | 2cposizioni | fisso | resistente alla polvere | circolare | resistente all\'acqua | Harmony | ghiera metallica cromata | solo testa | Selettore a chiave | XB4
Descrizione breve	Head for non illuminated push button, Harmony XB4, grey flush push button 22mm spring return unmarked
Descrizione estesa	This Harmony XB4, flush greybutton headoperates with a spring return / impulse mechanism. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is clearly distinguishable visually at a distance thanks to clear color. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	97.65
Codice TARIC	1741
Peso	0 kg