RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - ASTA AD IMPULSO NERA

Codice prodotto	SNRZB4BB2
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony XB4, black head operates with omnidirectional and spring return / impulse mechanism. This wobble stick head provides an ergonomic interface for controlling your machines. It is easily installed and replaced on compatible omnidirectional controllers. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a plastic bezel, this makes it ideal for applications requiring good resistance to chemical agents and/or double electrical insulation. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -25°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB4BB2
Codice produttore	ZB4BB2
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110173239
Classe ETIM	EC000632
Versione ETIM	10
Prezzo pubblico	68.10
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	2
Quantita minima	1
Quantita multipla	1
Quantita cartone	40
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	resistente agli urti | resistente alla polvere | XB4 | estrazione della chiave a sinistra | circolare | modulare | Selettore a chiave | solo testa | ghiera metallica cromata | nero | meccanismo ad impulso | chiave n.455 | resistente all\'acqua | 2 posizioni | Harmony
Descrizione breve	Head for joystick controller, Harmony XB4, black metal, 22mm, omnidirectional, spring return
Descrizione estesa	This Harmony XB4, black head operates with omnidirectional and spring return / impulse mechanism. This wobble stick head provides an ergonomic interface for controlling your machines. It is easily installed and replaced on compatible omnidirectional controllers. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a plastic bezel, this makes it ideal for applications requiring good resistance to chemical agents and/or double electrical insulation. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -25°C to 70°C allows versatility in usage of product.
Completezza BMEcat	100
Codice TARIC	1741
Peso	0 kg