RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA+BASE DI FISSAGGIO POTENZIO

Codice prodotto	SNRZB4BD922
Produttore	Telemecanique (Schneider)
Categoria	FISSAGGIO E SUPPORTI
Codice doganale	1741

DESCRIZIONE

This Harmony XB4, head and mounting base is used for potentiometer application. This head and mounting base for potentiometer provides an ergonomic external interface for controlling your machines thanks to its knurled knob head. It is ideal for controlling key parameters of automation components like drives and inverters and is easily installed and replaced on compatible potentiometers. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP65. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB4BD922
Codice produttore	ZB4BD922
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110896886
Classe ETIM	EC000222
Versione ETIM	10
Prezzo pubblico	63.60
Valuta	EUR

RIEPILOGO DATI DI CATALOGO

Moltiplicatore prezzo	1
Unita misura	PCE
Lead time	2
Quantita minima	1
Quantita multipla	1
Quantita cartone	80
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Chromium plated metal bezel | Harmony XB4 | Potentiometer | Head and mounting base | Water resistant | Head with operating shaftDust resistant | Impact resistant | Self-earthing
Descrizione breve	Potentiometer head, Harmony XB4, metal,black, 22mm, for use with 6.35mm shaft
Descrizione estesa	This Harmony XB4, head and mounting base is used for potentiometer application. This head and mounting base for potentiometer provides an ergonomic external interface for controlling your machines thanks to its knurled knob head. It is ideal for controlling key parameters of automation components like drives and inverters and is easily installed and replaced on compatible potentiometers. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP65. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	95.5
Codice TARIC	1741
Peso	0 kg