RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA PULSANTE GIALLO

Codice prodotto	SNRZB4BH05
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony XB4, flush yellow button head operates with a latched push-push mechanism. This button head provides an ergonomic interface for controlling your machines. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is clearly distinguishable visually at a distance thanks to clear color. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB4BH05
Codice produttore	ZB4BH05
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110122701
Classe ETIM	EC000221
Versione ETIM	10
Prezzo pubblico	15.04
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	2
Quantita minima	1
Quantita multipla	1
Quantita cartone	5
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	XB4 | ghiera metallica cromata | ad impulso | sporgente | resistente all\'acqua | solo testa | Harmony | Pulsante | modulare | resistente alla polvere | sistema di componenti a clip | con marcatura | marcatura "STOP" | rosso | circolare | resistente agli urti | messa a terra automatica
Descrizione breve	Head for illuminated push button, Harmony XB4, metal, yellow flush, 22mm, push-push, unmarked
Descrizione estesa	This Harmony XB4, flush yellow button head operates with a latched push-push mechanism. This button head provides an ergonomic interface for controlling your machines. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is clearly distinguishable visually at a distance thanks to clear color. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	97.65
Codice TARIC	1741
Peso	0 kg