# RIEPILOGO DATI DI CATALOGO

## Telemecanique (Schneider) - TESTA PULSANTE BIANCO

| | |
|---|---|
| **Codice prodotto** | SNRZB4BH13 |
| **Produttore** | Telemecanique (Schneider) |
| **Categoria** | ACCESSORI TELEMECANIQUE (SCHNEIDER) |
| **Codice doganale** | 1741 |

### DESCRIZIONE

This Harmony XB4, illuminated projecting white button head operates with latched push-push mechanism. This illuminated button head for universal LED provides a versatile interface for controlling your machines. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is clearly distinguishable visually at a distance thanks to illuminated, clear color and by touch due to projecting element, minimizing errors in machine control. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product. It provides high brightness for easy identification of function and operation mode, even in brightly lit environments.

### DATI DI CATALOGO

| | |
|---|---|
| **Sigla Metel** | SNR |
| **Codice Metel** | SNRZB4BH13 |
| **Codice produttore** | ZB4BH13 |
| **Marca** | Schneider Electric Spa |
| **Stato prodotto** | Stato Metel 6 |
| **Data ultimo aggiornamento** | LS |
| **Data certificazione** | 2026-09-10 |
| **Data variazione** | 2026-10-01 |
| **EAN** | 3389110890044 |
| **Classe ETIM** | EC000221 |
| **Versione ETIM** | 10 |
| **Prezzo pubblico** | 29.40 |
| **Valuta** | EUR |

# RIEPILOGO DATI DI CATALOGO

| | |
|---|---|
| **Moltiplicatore prezzo** | 1 |
| **Unita misura** | PCE |
| **Lead time** | 2 |
| **Quantita minima** | 1 |
| **Quantita multipla** | 1 |
| **Quantita cartone** | 100 |
| **Codice doganale** | Da verificare |
| **Famiglia statistica** | Comando |
| **Codice famiglia statistica** | AUTPEMCESCOM |
| **Keyword** | schneider electric \| dust-tight pushbutton head \| ik05 pushbutton head \| nema 4x pushbutton head \| nema 13 pushbutton head \| ip67 pushbutton head \| ip69k pushbutton head \| ip69 pushbutton head \| pushbutton spare parts \| pushbutton accessory \| se \| schneider \| switch head \| metal bezel pushbutton head \| pushbutton operator \| pushbutton actuator \| front element \| 22mm pushbutton head \| push-push head \| projecting pushbutton head \| white illuminated pushbutton head \| harmony xb4 pushbutton head |
| **Descrizione breve** | Head for illuminated push button, Harmony XB4, metal, white projecting, 22mm, push push, universal LED, unmarked |
| **Descrizione estesa** | This Harmony XB4, illuminated projecting white button head operates with latched push-push mechanism. This illuminated button head for universal LED provides a versatile interface for controlling your machines. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is clearly distinguishable visually at a distance thanks to illuminated, clear color and by touch due to projecting element, minimizing errors in machine control. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product. It provides high brightness for easy identification of function and operation mode, even in brightly lit environments. |
| **Completezza BMEcat** | 97.65 |
| **Codice TARIC** | 1741 |
| **Peso** | 0.05 kg |