RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA LAMPADA SPIA ROSSA LED

Codice prodotto	SNRZB4BV043E
Produttore	Telemecanique (Schneider)
Categoria	ILLUMINAZIONE
Codice doganale	1741

DESCRIZIONE

This Harmony XB4, plain lens head for pilot light with universal LED is red. It has a round shape and a chromium-plated metal bezel. This head for universal LED pilot light is designed to last without maintenance for a bright indicator of process and machine operations. The product is designed to use with legend insertion and is clearly distinguishable visually at a distance thanks to a clear color of len, enabling complex machine statuses to be read at a glance. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB4BV043E
Codice produttore	ZB4BV043E
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110290325
Classe ETIM	EC000223
Versione ETIM	10
Prezzo pubblico	5.95
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	7
Quantita minima	1
Quantita multipla	1
Quantita cartone	150
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	plain lens pilot light | round pilot light | integral red led pilot light | 22mm pilot light | pilot light complete unit | light signaling unit | indicator light complete | harmony xb4 pilot light | zamak collar pilot light | atex pilot light | dust-tight pilot light | 230V to 240V AC pilot light | metal bezel pilot light
Descrizione breve	Head for pilot light, Harmony XB4, red, 22mm, with plain lens, universal LED
Descrizione estesa	This Harmony XB4, plain lens head for pilot light with universal LED is red. It has a round shape and a chromium-plated metal bezel. This head for universal LED pilot light is designed to last without maintenance for a bright indicator of process and machine operations. The product is designed to use with legend insertion and is clearly distinguishable visually at a distance thanks to a clear color of len, enabling complex machine statuses to be read at a glance. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	96.67
Codice TARIC	1741
Peso	0 kg