RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA LAMPADA SPIA ARANCIO LED

Codice prodotto	SNRZB4BV053
Produttore	Telemecanique (Schneider)
Categoria	ILLUMINAZIONE
Codice doganale	1741

DESCRIZIONE

This Harmony XB4, plain lens head for pilot light with universal LED is orange. This head for universal LED pilot light is designed to last without maintenance for a bright indicator of process and machine operations. It is clearly distinguishable visually at a distance thanks to a clear color of len, enabling complex machine statuses to be read at a glance. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB4BV053
Codice produttore	ZB4BV053
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110894981
Classe ETIM	EC000223
Versione ETIM	10
Prezzo pubblico	5.66
Valuta	EUR
Moltiplicatore prezzo	1

RIEPILOGO DATI DI CATALOGO

Unita misura	PCE
Lead time	4
Quantita minima	1
Quantita multipla	1
Quantita cartone	5
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Harmony XB4 | Impact resistant | Dust resistant | Orangeuniversal LED | Plain lens | Water resistant | Chromium plated metal bezel | Head only | Pilot light
Descrizione breve	Head for pilot light, Harmony XB4, metal, orange, 22mm, universal LED, plain lens
Descrizione estesa	This Harmony XB4, plain lens head for pilot light with universal LED is orange. This head for universal LED pilot light is designed to last without maintenance for a bright indicator of process and machine operations. It is clearly distinguishable visually at a distance thanks to a clear color of len, enabling complex machine statuses to be read at a glance. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	96.67
Codice TARIC	1741
Peso	0.027 kg