RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA LAMPADA SPIA GIALLA LED

Codice prodotto	SNRZB4BV083
Produttore	Telemecanique (Schneider)
Categoria	ILLUMINAZIONE
Codice doganale	1741

DESCRIZIONE

This Harmony XB4, plain lens head for pilot light with universal LED is yellow and has a round shape. It is clearly distinguishable visually at a distance thanks to a clear color of len, enabling complex machine statuses to be read at a glance. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB4BV083
Codice produttore	ZB4BV083
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3606481202253
Classe ETIM	EC000223
Versione ETIM	10
Prezzo pubblico	5.66
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	2
Quantita minima	1
Quantita multipla	1
Quantita cartone	300
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	22mm pilot light | pilot light complete unit | light signaling unit | indicator light complete | harmony xb4 pilot light | round pilot light | integral yellow led pilot light | metal bezel pilot light | plain lens pilot light | 230V to 240V AC pilot light | dust-tight pilot light | atex pilot light | zamak collar pilot light
Descrizione breve	Head for pilot light, Harmony XB4, yellow, 22mm, with plain lens, universal LED
Descrizione estesa	This Harmony XB4, plain lens head for pilot light with universal LED is yellow and has a round shape. It is clearly distinguishable visually at a distance thanks to a clear color of len, enabling complex machine statuses to be read at a glance. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a metal bezel, this makes it Ideal for applications requiring high impact and vibration resistance. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	96.67
Codice TARIC	1741
Peso	0 kg