RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - CORPO LAMPADA SPIA

Codice prodotto	SNRZB4BV8
Produttore	Telemecanique (Schneider)
Categoria	ILLUMINAZIONE
Codice doganale	1741

DESCRIZIONE

This Harmony XB4, light block with body/fixing collar operates with BA9s base Integral LED. It has a metal body and is compatible with Harmony XB4 pilot lights. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by BA9s base Integral LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. It is designed to fit with a standard 22mm control and signaling units, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 55°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB4BV8
Codice produttore	ZB4BV8
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110889673
Classe ETIM	EC000204
Versione ETIM	10
Prezzo pubblico	52.95
Valuta	EUR
Moltiplicatore prezzo	1

RIEPILOGO DATI DI CATALOGO

Unita misura	PCE
Lead time	2
Quantita minima	1
Quantita multipla	1
Quantita cartone	50
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Light block | Metal bezel | Clip-together component system | BA9s base integral LED | Dust resistant | Harmony XB4 | with body/fixing collar | Screw clamp terminal connections | Self-earthing | Impact resistant
Descrizione breve	Light block with body fixing collar, Harmony XB4, metal, with BA9s bulb, 440...480V AC
Descrizione estesa	This Harmony XB4, light block with body/fixing collar operates with BA9s base Integral LED. It has a metal body and is compatible with Harmony XB4 pilot lights. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by BA9s base Integral LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. It is designed to fit with a standard 22mm control and signaling units, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 55°C allows versatility in usage of product.
Completezza BMEcat	99.38
Codice TARIC	1741
Peso	0 kg