RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - CORPO CONTATTI

Codice prodotto	SNRZB4BZ141
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony XB4, single contact block is pre-assembled on a body/collar fixing unit. It has 1 x NO + 2 x NC contacts and a chromium-plated metal bezel. It is compatible with Harmony XB4 This body fixing collar is pre-mounted with a contact block. Simply adding a head to this assembly will provide you with a complete ready-to-use push button. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance provides less maintenance and damage in your installation. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB4BZ141
Codice produttore	ZB4BZ141
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110889420
Classe ETIM	EC000041
Versione ETIM	10
Prezzo pubblico	20.30
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	2
Quantita minima	1
Quantita multipla	1
Quantita cartone	5
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Self-earthing | Impact resistant | Dust resistant | N/C contact | N/O contact | Snap-fit assembly | Water resistant | Chromium plated metal bezel | with body/fixing collar | Single contact | Contact block | Harmony XB4 | Screw clamp terminal connections
Descrizione breve	Single contact block with body fixing collar, Harmony XB4, metal, screw clamp terminal, 1NO+2NC
Descrizione estesa	This Harmony XB4, single contact block is pre-assembled on a body/collar fixing unit. It has 1 x NO + 2 x NC contacts and a chromium-plated metal bezel. It is compatible with Harmony XB4 This body fixing collar is pre-mounted with a contact block. Simply adding a head to this assembly will provide you with a complete ready-to-use push button. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance provides less maintenance and damage in your installation. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	100
Codice TARIC	1741
Peso	0 kg