RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA PULSANTE NERO

Codice prodotto	SNRZB5AA2
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony XB5, flush black button head operates with a spring return mechanism. This button head provides an ergonomic interface for controlling your machines. It is easily installed and replaced on compatible complete push-button units and contact blocks via snap-fit assembly. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66 / IP67 / IP69 / IP69K. It has a plastic bezel, this makes it ideal for applications requiring good resistance to chemical agents and/or double electrical insulation. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB5AA2
Codice produttore	ZB5AA2
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110904437
Classe ETIM	EC000221
Versione ETIM	10
Prezzo pubblico	6.45
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	4
Quantita minima	1
Quantita multipla	1
Quantita cartone	300
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Spring return | Double insulated plastic bezel | Water resistant | Clip-together component system | Flush pushbutton | Harmony XB5 | Head only | Pushbutton | Push-Button | Black pushbutton | Dust resistant | Impact resistant | Self-earthing | Screw clamp terminal connection | Push Button
Descrizione breve	Head for non illuminated push button, Harmony XB5, plastic, flush, black, 22mm, spring return, unmarked
Descrizione estesa	This Harmony XB5, flush black button head operates with a spring return mechanism. This button head provides an ergonomic interface for controlling your machines. It is easily installed and replaced on compatible complete push-button units and contact blocks via snap-fit assembly. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66 / IP67 / IP69 / IP69K. It has a plastic bezel, this makes it ideal for applications requiring good resistance to chemical agents and/or double electrical insulation. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	97.65
Codice TARIC	1741
Peso	0 kg