RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA PULSANTE BLU

Codice prodotto	SNRZB5AA651
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony XB5, flush blue button head operates with a spring return / impulse mechanism. This button head provides an ergonomic interface for controlling your machines. It is easily installed and replaced on compatible complete push-button units and contact blocks via snap-fit assembly. It is clearly distinguishable visually at a distance thanks to clear color and marking. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a plastic bezel, this makes it ideal for applications requiring good resistance to chemical agents and/or double electrical insulation. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB5AA651
Codice produttore	ZB5AA651
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3606480939822
Classe ETIM	EC000221
Versione ETIM	10
Prezzo pubblico	7.40
Valuta	EUR
Moltiplicatore prezzo	1

RIEPILOGO DATI DI CATALOGO

Unita misura	PCE
Lead time	2
Quantita minima	1
Quantita multipla	1
Quantita cartone	50
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	modulare | antipolvere | Harmony | XB5 | Pulsante | solo testa | passo-passo | doppia ghiera in plastica isolata | impermeabile | sistema di componenti a clip | a filo ghiera | senza marcatura | bianco | circolare | resistente agli urti
Descrizione breve	Head for non illuminated push button, Harmony XB5, blue resseced, 22mm, spring return, marked up and down arrow
Descrizione estesa	This Harmony XB5, flush blue button head operates with a spring return / impulse mechanism. This button head provides an ergonomic interface for controlling your machines. It is easily installed and replaced on compatible complete push-button units and contact blocks via snap-fit assembly. It is clearly distinguishable visually at a distance thanks to clear color and marking. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a plastic bezel, this makes it ideal for applications requiring good resistance to chemical agents and/or double electrical insulation. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	97.65
Codice TARIC	1741
Peso	0 kg