RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA PULSANTE BLU

Codice prodotto	SNRZB5AA68
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This blue flush button head with transparent cap provides an ergonomic interface for controlling your machines. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is used for insertion of legend. It is clearly distinguishable visually at a distance thanks to its clear color. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP69K. It makes it ideal for operation in harsh environments.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB5AA68
Codice produttore	ZB5AA68
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110904765
Classe ETIM	EC000221
Versione ETIM	10
Prezzo pubblico	9.44
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE
Lead time	2

RIEPILOGO DATI DI CATALOGO

Quantita minima	1
Quantita multipla	1
Quantita cartone	150
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	NO contact | blue flush pushbutton | Spring Return | Plastic Pushbutton | Illumunated selector head pushbutton | clear boot pushbutton | Push Button | 22mm Mounting Diameter | Push-Button | Pushbutton | Schneider Electric | se | Harmony XB5 | Harmony
Descrizione breve	Head for illuminated push button, Harmony XB5, plastic, blue flush, 22mm, universal LED, for insetion of legend
Descrizione estesa	This blue flush button head with transparent cap provides an ergonomic interface for controlling your machines. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is used for insertion of legend. It is clearly distinguishable visually at a distance thanks to its clear color. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP69K. It makes it ideal for operation in harsh environments.
Completezza BMEcat	97.65
Codice TARIC	1741
Peso	0 kg