RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA SELETTORE A CHIAVE 2 POSIZIONI

Codice prodotto	SNRZB5AG612
Produttore	Telemecanique (Schneider)
Categoria	CHIUSURE E CHIAVI
Codice doganale	1741

DESCRIZIONE

This head with key (key no.421E) provides a versatile interface for controlling your machines. It is easily installed and replaced on compatible complete key selector switch units. It provides a secure manner for authorized staff to switch between process or machine operating modes. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB5AG612
Codice produttore	ZB5AG612
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110135220
Classe ETIM	EC000222
Versione ETIM	10
Prezzo pubblico	58.40
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE
Lead time	2

RIEPILOGO DATI DI CATALOGO

Quantita minima	1
Quantita multipla	1
Quantita cartone	50
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	22mm mounting diameter | Double insulated plastic bezel | Head only | Key switch | XB5 | Harmony | Schneider Electric | Modular | Impact resistant | Dust resistant | Circular | Key no. 421E | Left position key withdrawal | 2-position | Spring Return from right to left | Water resistant
Descrizione breve	Head for key selector switch, Harmony XB5, plastic, black, 22mm, key 421E, 2 positions, spring return right to left
Descrizione estesa	This head with key (key no.421E) provides a versatile interface for controlling your machines. It is easily installed and replaced on compatible complete key selector switch units. It provides a secure manner for authorized staff to switch between process or machine operating modes. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.
Completezza BMEcat	95.5
Codice TARIC	1741
Peso	0 kg