RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA PULSANTE LUMINOSO BLU

Codice prodotto	SNRZB5AH063
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This blue flush illuminated button head for universal LED provides a versatile interface for controlling your machines. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is very distinguishable visually at a distance thanks to illuminated, clear color and by touch due to flush element. It minimizes errors in machine control. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB5AH063
Codice produttore	ZB5AH063
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110137859
Classe ETIM	EC000221
Versione ETIM	10
Prezzo pubblico	20.10
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE
Lead time	2

RIEPILOGO DATI DI CATALOGO

Quantita minima	1
Quantita multipla	1
Quantita cartone	300
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Impact resistant | Schneider Electric | Harmony | XB5 | Push-Button | Pushbutton | Push Button | Head only | Push-push | Double insulated plastic bezel | Water resistant | Clip-together component system | Illuminated | Flush | Unmarked | blue | Circular | universal LED | Dust resistant | Modular
Descrizione breve	Head for illuminated push button, Harmony XB5, blue flush, 22mm, universal LED, push to release, unmarked
Descrizione estesa	This blue flush illuminated button head for universal LED provides a versatile interface for controlling your machines. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is very distinguishable visually at a distance thanks to illuminated, clear color and by touch due to flush element. It minimizes errors in machine control. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.
Completezza BMEcat	97.65
Codice TARIC	1741
Peso	0 kg