RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA PULSANTE ROSSO

Codice prodotto	SNRZB5AL4
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This red projecting button head provides an ergonomic interface for controlling your machines. It is easily combined with Harmony range of push buttons and contact blocks. Thus it is possible to perform a large variety of control functions. It is clearly distinguishable visually at a distance thanks to its clear color. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB5AL4
Codice produttore	ZB5AL4
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110906455
Classe ETIM	EC000221
Versione ETIM	10
Prezzo pubblico	8.50
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE
Lead time	2

RIEPILOGO DATI DI CATALOGO

Quantita minima	1
Quantita multipla	1
Quantita cartone	300
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Push-Button | Double insulated plastic bezel | Water resistant | Clip-together component system | Projecting | Unmarked | Red | Circular | Dust resistant | Impact resistant | Modular | Schneider Electric | Harmony | XB5 | Head only | Spring return | Pushbutton | Push Button
Descrizione breve	Head for non illuminated push button, Harmony XB5, plastic, projecting, red, 22mm, spring return, unmarked
Descrizione estesa	This red projecting button head provides an ergonomic interface for controlling your machines. It is easily combined with Harmony range of push buttons and contact blocks. Thus it is possible to perform a large variety of control functions. It is clearly distinguishable visually at a distance thanks to its clear color. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.
Completezza BMEcat	97.65
Codice TARIC	1741
Peso	0 kg