RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA PULSANTE VERDE IN GOMMA

Codice prodotto	SNRZB5AP3S
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This green colored silicone booted button head provides an ergonomic interface for controlling your machine . It provides also a simple solution to prevent dirt and other contaminants. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB5AP3S
Codice produttore	ZB5AP3S
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110999389
Classe ETIM	EC000221
Versione ETIM	10
Prezzo pubblico	12.11
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	2
Quantita minima	1
Quantita multipla	1
Quantita cartone	200
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Green pushbutton | Flush pushbutton | Colored silicone boot | Clip-together component system | Water resistant | Double insulated plastic bezel | Spring return | Dust resistant | Pushbutton | Impact resistant | Push Button | Head only | Harmony XB5 | Push-Button
Descrizione breve	Head for non illuminated push button, Harmony XB5, plastic, flush, green, 22mm, spring return, coloured boot, unmarked
Descrizione estesa	This green colored silicone booted button head provides an ergonomic interface for controlling your machine . It provides also a simple solution to prevent dirt and other contaminants. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.
Completezza BMEcat	97.65
Codice TARIC	1741
Peso	0 kg