RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA LAMPADA SPIA BIANCA

Codice prodotto	SNRZB5AV01
Produttore	Telemecanique (Schneider)
Categoria	ILLUMINAZIONE
Codice doganale	1741

DESCRIZIONE

This Harmony XB5 plain lens white head for pilot light is supplied with BA9s base. It offers a bright indicator of process and machine operations. It is clearly distinguishable visually at a distance thanks to a clear color of lens. It enables complex machine statuses to be read at a glance. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB5AV01
Codice produttore	ZB5AV01
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110908053
Classe ETIM	EC000223
Versione ETIM	10
Prezzo pubblico	5.06
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE
Lead time	2

RIEPILOGO DATI DI CATALOGO

Quantita minima	1
Quantita multipla	1
Quantita cartone	300
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	ip67 pilot light head | 22mm pilot light head | front element | plastic bezel pilot light headplain lens | BA9s bulb | lighting accessories | ip66 pilot light head | ip69 pilot light head | signaling light head | pilot light head | Harmony XB5 | ip69k pilot light head | ik05 pilot light head | dust-tight pilot light head
Descrizione breve	Head for pilot light, Harmony XB5, plastic, white, 22mm, plain lens, BA9s base fitting
Descrizione estesa	This Harmony XB5 plain lens white head for pilot light is supplied with BA9s base. It offers a bright indicator of process and machine operations. It is clearly distinguishable visually at a distance thanks to a clear color of lens. It enables complex machine statuses to be read at a glance. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.
Completezza BMEcat	96.67
Codice TARIC	1741
Peso	0 kg