RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA LAMPADA SPIA BLU LED

Codice prodotto	SNRZB5AV063
Produttore	Telemecanique (Schneider)
Categoria	ILLUMINAZIONE
Codice doganale	1741

DESCRIZIONE

This Harmony XB5, plain lens head for pilot light with universal LED is blue. This head for universal LED pilot light is designed to last without maintenance for a bright indicator of process and machine operations. It is clearly distinguishable visually at a distance thanks to a clear color of len, enabling complex machine statuses to be read at a glance. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a plastic bezel, this makes it ideal for applications requiring good resistance to chemical agents and/or double electrical insulation. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB5AV063
Codice produttore	ZB5AV063
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110908145
Classe ETIM	EC000223
Versione ETIM	10
Prezzo pubblico	5.06
Valuta	EUR
Moltiplicatore prezzo	1

RIEPILOGO DATI DI CATALOGO

Unita misura	PCE
Lead time	4
Quantita minima	1
Quantita multipla	1
Quantita cartone	300
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Plain lens | Impact resistant | Dust resistant | blueuniversal LED | Water resistant | Chromium plated plastic bezel | Head only | Pilot light | Harmony XB5
Descrizione breve	Head for pilot light, Harmony XB5, plastic, blue, 22mm, plain lens, BA9s base fitting
Descrizione estesa	This Harmony XB5, plain lens head for pilot light with universal LED is blue. This head for universal LED pilot light is designed to last without maintenance for a bright indicator of process and machine operations. It is clearly distinguishable visually at a distance thanks to a clear color of len, enabling complex machine statuses to be read at a glance. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a plastic bezel, this makes it ideal for applications requiring good resistance to chemical agents and/or double electrical insulation. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	96.67
Codice TARIC	1741
Peso	0 kg