# RIEPILOGO DATI DI CATALOGO

## Telemecanique (Schneider) - TESTA PULSANTE LUMINOSO ROSSO LED

| | |
|---|---|
| **Codice prodotto** | SNRZB5AW343 |
| **Produttore** | Telemecanique (Schneider) |
| **Categoria** | ACCESSORI TELEMECANIQUE (SCHNEIDER) |
| **Codice doganale** | 1741 |

### DESCRIZIONE

This Harmony XB5, plain lens illuminated red flush head for universal LED operates with a spring return / impulse mechanism. This illuminated button head for universal LED provides a versatile interface for controlling your machines. It is easily installed and replaced on compatible complete push-button units and contact blocks via snap-fit assembly. It is clearly distinguishable visually at a distance thanks to illuminated, clear color and by touch due to flush element, minimizing errors in machine control. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a plastic bezel, this makes it ideal for applications requiring good resistance to chemical agents and/or double electrical insulation. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product. It provides high brightness for easy identification of function and operation mode, even in brightly lit environments.

### DATI DI CATALOGO

| | |
|---|---|
| **Sigla Metel** | SNR |
| **Codice Metel** | SNRZB5AW343 |
| **Codice produttore** | ZB5AW343 |
| **Marca** | Schneider Electric Spa |
| **Stato prodotto** | Stato Metel 3 |
| **Data ultimo aggiornamento** | LS |
| **Data certificazione** | 2026-09-10 |
| **Data variazione** | 2026-10-01 |
| **EAN** | 3389110909968 |
| **Classe ETIM** | EC000221 |
| **Versione ETIM** | 10 |
| **Prezzo pubblico** | 11.10 |

# RIEPILOGO DATI DI CATALOGO

| | |
|---|---|
| **Valuta** | EUR |
| **Moltiplicatore prezzo** | 1 |
| **Unita misura** | PCE |
| **Lead time** | 2 |
| **Quantita minima** | 1 |
| **Quantita multipla** | 1 |
| **Quantita cartone** | 300 |
| **Codice doganale** | Da verificare |
| **Famiglia statistica** | Comando |
| **Codice famiglia statistica** | AUTPEMCESCOM |
| **Keyword** | Red pushbutton \| Pushbutton \| Double insulated plastic bezel \| Water resistant \| Clip-together component system \| Illuminated pushbutton \| Push Button \| Plain lens \| Flush pushbutton \| Spring return \| Impact resistant \| Head only \| Harmony XB5 \| Dust resistant \| Push-Button \| universal LED |
| **Descrizione breve** | Head for illuminated push button, Harmony XB5, plastic, red flush, 22mm, universal LED, spring return, plain lens |
| **Descrizione estesa** | This Harmony XB5, plain lens illuminated red flush head for universal LED operates with a spring return / impulse mechanism. This illuminated button head for universal LED provides a versatile interface for controlling your machines. It is easily installed and replaced on compatible complete push-button units and contact blocks via snap-fit assembly. It is clearly distinguishable visually at a distance thanks to illuminated, clear color and by touch due to flush element, minimizing errors in machine control. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It has a plastic bezel, this makes it ideal for applications requiring good resistance to chemical agents and/or double electrical insulation. It is designed to fit in a standard 22mm cutout, ensuring compatibility when installing in pre-existing machinery. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product. It provides high brightness for easy identification of function and operation mode, even in brightly lit environments. |
| **Completezza BMEcat** | 97.65 |
| **Codice TARIC** | 1741 |
| **Peso** | 0 kg |