RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA PULSANTE A FUNGO ROSSO

Codice prodotto	SNRZB5AW743
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This red illuminated 40mm mushroom shape button head for universal LED is ideal when quick actions are required. It fits for a process or machine to function correctly or where operator movements require highest ergonomy. It is easily combined with Harmony range of contact blocks to perform a large variety of control functions. It is clearly distinguishable visually at a distance thanks to its illuminated head. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB5AW743
Codice produttore	ZB5AW743
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110666854
Classe ETIM	EC001038
Versione ETIM	10
Prezzo pubblico	28.45
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	4
Quantita minima	1
Quantita multipla	1
Quantita cartone	120
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Double insulated plastic bezel | Clip-together component system | Push Button | Water resistant | Turn to release | Head only | Impact resistant | Illuminated | Mushroom headReduniversal LED | Dust resistant | Harmony XB5 | Push-Button | Pushbutton
Descrizione breve	Head for illuminated emergency switching off push button, Harmony XB5, plastic, red mushroom 40mm, 22mm, universal LED, turn to release
Descrizione estesa	This red illuminated 40mm mushroom shape button head for universal LED is ideal when quick actions are required. It fits for a process or machine to function correctly or where operator movements require highest ergonomy. It is easily combined with Harmony range of contact blocks to perform a large variety of control functions. It is clearly distinguishable visually at a distance thanks to its illuminated head. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.
Completezza BMEcat	96.21
Codice TARIC	1741
Peso	0 kg