RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA PULSANTE A FUNGO GIALLO

Codice prodotto	SNRZB5AW753
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This orange illuminated 40mm mushroom shape button head for universal LED is ideal when quick actions are required. It fits for a process or machine to function correctly or where operator movements require highest ergonomy. It is easily combined with Harmony range of contact blocks to perform a large variety of control functions. It is clearly distinguishable visually at a distance thanks to its illuminated head. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB5AW753
Codice produttore	ZB5AW753
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110666861
Classe ETIM	EC001038
Versione ETIM	10
Prezzo pubblico	28.45
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	2
Quantita minima	1
Quantita multipla	1
Quantita cartone	40
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Pushbutton | Circular | green | Plain lens | universal LED | Dust resistant | Unmarked | Double insulated plastic bezel | Spring return | Head only | Push Button | clear boot head | Modular | Impact resistant | Water resistant | Clip-together component system | Illuminated | Flush | Schneider Electric | Harmony | XB5 | Push-Button
Descrizione breve	Head for illuminated push button, Harmony XB5, plastic, orange mushroom 40mm, 22mm, latching turn to release, clear boot
Descrizione estesa	This orange illuminated 40mm mushroom shape button head for universal LED is ideal when quick actions are required. It fits for a process or machine to function correctly or where operator movements require highest ergonomy. It is easily combined with Harmony range of contact blocks to perform a large variety of control functions. It is clearly distinguishable visually at a distance thanks to its illuminated head. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.
Completezza BMEcat	96.21
Codice TARIC	1741
Peso	0 kg