RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TESTA PULSANTE LUMINOSO ROSSO

Codice prodotto	SNRZB5CW343
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This red flush illuminated button head provides a versatile interface for controlling your machines. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is very distinguishable visually at a distance thanks to illuminated, clear color and by touch due to flush element. It minimizes errors in machine control. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZB5CW343
Codice produttore	ZB5CW343
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110934847
Classe ETIM	EC000221
Versione ETIM	10
Prezzo pubblico	13.69
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	4
Quantita minima	1
Quantita multipla	1
Quantita cartone	5
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Dust resistant | Schneider Electric | Harmony | XB5 | Pilot light | Head only | Double insulated plastic bezel | Water resistant | Plain lens | Modular | Impact resistant | Circular | universal LED | red
Descrizione breve	Head for illuminated push button, Harmony XB5, red square square flush 22mm, universal LED, for insertion of legend
Descrizione estesa	This red flush illuminated button head provides a versatile interface for controlling your machines. It is easily installed and replaced on compatible complete push button units and contact blocks via snap-fit assembly. It is very distinguishable visually at a distance thanks to illuminated, clear color and by touch due to flush element. It minimizes errors in machine control. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It makes it ideal for operation in harsh environments.
Completezza BMEcat	97.65
Codice TARIC	1741
Peso	0 kg