RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - FALSO CONTATTO

Codice prodotto	SNRZBE000
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony ZB, dummy contact block uses PCB terminals. This contact block is designed as a dummy contact block housing without pins. It is easily installed and connected to Harmony XB4 and XB5 transformer block for light block with integral LED with simple PCB connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance under 6A load allows less maintenance and damage in your installation. It has clear color scheme for NO and NC contact block types. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBE000
Codice produttore	ZBE000
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110516845
Classe ETIM	EC002024
Versione ETIM	10
Prezzo pubblico	118.50
Valuta	EUR
Moltiplicatore prezzo	100
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	7
Quantita minima	5
Quantita multipla	5
Quantita cartone	800
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	montaggio a scatto | resistente all\'urto | XB4 | collegamenti con morsetti a molla | XB5 | elemento di contatto | modulare | contatto dummy | Harmony | tenuta alla polvere
Descrizione breve	Dummy contact block, Harmony XB4, for head 16mm without pins for PCB
Descrizione estesa	This Harmony ZB, dummy contact block uses PCB terminals. This contact block is designed as a dummy contact block housing without pins. It is easily installed and connected to Harmony XB4 and XB5 transformer block for light block with integral LED with simple PCB connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance under 6A load allows less maintenance and damage in your installation. It has clear color scheme for NO and NC contact block types. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	98
Codice TARIC	1741
Peso	0 kg