RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - ELEMENTO DI CONTATTO NC

Codice prodotto	SNRZBE102
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony ZB, XB5 single contact block contact block uses screw clamp terminals. This contact block allows fast and easy replacement and configuration of your push buttons and selector switches. It is easily installed and replaced on XB5 complete push-button units and selector switches via a clip assembly and connects to control circuits with simple screw-clamp connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance under 6A load allows less maintenance and damage in your installation. It has clear color scheme for NO and NC contact block types. Vibration resistant screw clamp connection terminals ensure high vibration resistance making product suitable installation on high impact machine.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBE102
Codice produttore	ZBE102
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110089486
Classe ETIM	EC000041
Versione ETIM	10
Prezzo pubblico	5.49
Valuta	EUR
Moltiplicatore prezzo	1

RIEPILOGO DATI DI CATALOGO

Unita misura	PCE
Lead time	4
Quantita minima	5
Quantita multipla	5
Quantita cartone	800
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Clip-together component system | Single contact | Harmony XB5 | Contact block | Dust resistant | Harmony XB4 | N/C contact | Self-earthing | Impact resistant | Screw clamp terminal connection
Descrizione breve	Single contact block, Harmony XB4, silver alloy, screw clamp terminal, 1NC
Descrizione estesa	This Harmony ZB, XB5 single contact block contact block uses screw clamp terminals. This contact block allows fast and easy replacement and configuration of your push buttons and selector switches. It is easily installed and replaced on XB5 complete push-button units and selector switches via a clip assembly and connects to control circuits with simple screw-clamp connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance under 6A load allows less maintenance and damage in your installation. It has clear color scheme for NO and NC contact block types. Vibration resistant screw clamp connection terminals ensure high vibration resistance making product suitable installation on high impact machine.
Completezza BMEcat	100
Codice TARIC	1741
Peso	0.01 kg