RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - ELEMENTO DI CONTATTO CONNETTORE

Codice prodotto	SNRZBE1024
Produttore	Telemecanique (Schneider)
Categoria	PRESE E CONNESSIONI
Codice doganale	1741

DESCRIZIONE

This Harmony ZB, single contact block uses plug-in terminals. It is compatible with Harmony XB4 and XB5 control and signaling units. This contact block allows fast and easy replacement and configuration of your push buttons and selector switches. It is easily installed and replaced on XB4 and XB5 complete push-button units and selector switches and connects to control circuits with simple plug-in connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance under 6A load allows less maintenance and damage in your installation. It has clear color scheme for NO and NC contact block types. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBE1024
Codice produttore	ZBE1024
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110089509
Classe ETIM	EC000041
Versione ETIM	10
Prezzo pubblico	6.16
Valuta	EUR
Moltiplicatore prezzo	1

RIEPILOGO DATI DI CATALOGO

Unita misura	PCE
Lead time	7
Quantita minima	5
Quantita multipla	5
Quantita cartone	800
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	contact block with plug-in connector | single contact block for pushbutton | contact block for selector switch | contact block for 22mm head | Harmony XB4 | Harmony XB5 | contact block for pushbutton | Harmony XB4 | Harmony XB5
Descrizione breve	Contact block, Harmony XB4, Harmony XB5, single contact, for head 22mm, standard contacts, plug in connector, 1NC
Descrizione estesa	This Harmony ZB, single contact block uses plug-in terminals. It is compatible with Harmony XB4 and XB5 control and signaling units. This contact block allows fast and easy replacement and configuration of your push buttons and selector switches. It is easily installed and replaced on XB4 and XB5 complete push-button units and selector switches and connects to control circuits with simple plug-in connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance under 6A load allows less maintenance and damage in your installation. It has clear color scheme for NO and NC contact block types. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	100
Codice TARIC	1741
Peso	0 kg