RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - ELEMENTO DI CONTATTO

Codice prodotto	SNRZBE1029
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony ZB, single contact block uses lugs terminals. It is compatible with Harmony XB4 and XB5 control and signaling units. This contact block allows fast and easy replacement and configuration of your push buttons and selector switches. It is easily installed and replaced on XB4 and XB5 complete push-button units and selector switches and connects to control circuits with simple lugs connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance under 6A load allows less maintenance and damage in your installation. It has clear color scheme for NO and NC contact block types. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBE1029
Codice produttore	ZBE1029
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110177473
Classe ETIM	EC000041
Versione ETIM	10
Prezzo pubblico	6.51
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	7
Quantita minima	5
Quantita multipla	5
Quantita cartone	800
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Harmony XB4 | Dust resistant | Impact resistantLugs terminal connections | Single contact | Snap-fit assembly | N/C contact | Harmony XB5 | Contact block
Descrizione breve	Single contact block, Harmony XB4, silver alloy, screw terminals for lug, 1NC
Descrizione estesa	This Harmony ZB, single contact block uses lugs terminals. It is compatible with Harmony XB4 and XB5 control and signaling units. This contact block allows fast and easy replacement and configuration of your push buttons and selector switches. It is easily installed and replaced on XB4 and XB5 complete push-button units and selector switches and connects to control circuits with simple lugs connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance under 6A load allows less maintenance and damage in your installation. It has clear color scheme for NO and NC contact block types. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	100
Codice TARIC	1741
Peso	0 kg