RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - ELEMENTO CONTATTO NO SCALATO

Codice prodotto	SNRZBE201
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony ZB, single contact block for staggered early make contact uses screw-clamp terminals. It is compatible with Harmony XB4 and XB5 control and signaling units. This contact block, uses for staggered early make contact operation, allows fast and easy replacement and configuration of specific control and signaling products. It is easily installed and replaced on XB4 and XB5 control and signalling units and connects to control circuits with screw-clamp connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance under 6A load allows less maintenance and damage in your installation. It has clear color scheme for NO and NC contact block types. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBE201
Codice produttore	ZBE201
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110177442
Classe ETIM	EC000041
Versione ETIM	10
Prezzo pubblico	7.52
Valuta	EUR

RIEPILOGO DATI DI CATALOGO

Moltiplicatore prezzo	1
Unita misura	PCE
Lead time	2
Quantita minima	5
Quantita multipla	5
Quantita cartone	800
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Single contact | Harmony XB4 | Harmony XB5 | Contact block | Staggered contact | Chromium plated metal bezel | Water resistant | Snap-fit assembly | N/O contact | Early make | Dust resistant | Impact resistant | Screw clamp terminal connections
Descrizione breve	Single contact block, Harmony XB4, silver alloy, screw clamp terminal, early make 1NO
Descrizione estesa	This Harmony ZB, single contact block for staggered early make contact uses screw-clamp terminals. It is compatible with Harmony XB4 and XB5 control and signaling units. This contact block, uses for staggered early make contact operation, allows fast and easy replacement and configuration of specific control and signaling products. It is easily installed and replaced on XB4 and XB5 control and signalling units and connects to control circuits with screw-clamp connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance under 6A load allows less maintenance and damage in your installation. It has clear color scheme for NO and NC contact block types. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	100
Codice TARIC	1741
Peso	0 kg