RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - ELEMENTO DI CONTATTO 2NO

Codice prodotto	SNRZBE503
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony ZB, single contact block for high power switching uses screw-clamp terminals. It is compatible with Harmony XB4 and XB5 control and signaling units. This contact block, uses for high power switching contact, allows fast and easy replacement and configuration of specific control and signaling products. It is easily installed and replaced on XB4 and XB5 control and signalling units and connects to control circuits with simple screw-clamp connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance under 6A load allows less maintenance and damage in your installation. It has clear color scheme for NO and NC contact block types. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBE503
Codice produttore	ZBE503
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389119042239
Classe ETIM	EC000041
Versione ETIM	10
Prezzo pubblico	12.36
Valuta	EUR
Moltiplicatore prezzo	1

RIEPILOGO DATI DI CATALOGO

Unita misura	PCE
Lead time	B
Quantita minima	1
Quantita multipla	1
Quantita cartone	80
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Contact block | Harmony XB5 | Harmony XB4 | High power switching contacts block | Chromium plated metal bezel | Snap-fit assembly | 2 NO contact | Dust resistant | Impact resistant | Screw clamp terminal connections
Descrizione breve	High power switching contact block, Harmony XB4, silver alloy, screw clamp terminal, 2NO
Descrizione estesa	This Harmony ZB, single contact block for high power switching uses screw-clamp terminals. It is compatible with Harmony XB4 and XB5 control and signaling units. This contact block, uses for high power switching contact, allows fast and easy replacement and configuration of specific control and signaling products. It is easily installed and replaced on XB4 and XB5 control and signalling units and connects to control circuits with simple screw-clamp connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance under 6A load allows less maintenance and damage in your installation. It has clear color scheme for NO and NC contact block types. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	100
Codice TARIC	1741
Peso	0 kg