RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - INTERRUTTORE FUNE WIRELESS

Codice prodotto	SNRZBRP1
Produttore	Telemecanique (Schneider)
Categoria	PROTEZIONE ELETTRICA
Codice doganale	1741

DESCRIZIONE

This rope pull switch is part of the range Harmony XB5R plastic and XB4R metal wireless and batteryless pushbuttons. It features a rope pull switch with wireless and batteryless transmitter. Its pulling force is from 45N to 1000N. The rope pull switch is adapted for automatic doors. It sends a radio message to the receiver in the control panel to open and close the door. It operates with the protocol Zigbee green power 2.4 GHz in compliance with IEEE 802.15.4. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It weighs 150g.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBRP1
Codice produttore	ZBRP1
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3606480571732
Classe ETIM	EC002026
Versione ETIM	10
Prezzo pubblico	92.20
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	2
Quantita minima	1
Quantita multipla	1
Quantita cartone	32
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	5mhz wireless package | 16 channel transmitter | zigbee wireless transmitter | rope pull switch transmitter | omnidirectional antenna transmitter | 2.4GHz transmitter | rope pull switch with transmitter | Harmony XB5R | plastic bezel rope pull switch | ip66 rope pull switch | wireless and batteryless rope pull switch | remote control station transmitter | nema4x rope pull switch | dust-tight rope pull switch | ik05 rope pull switch
Descrizione breve	Rope pull switch with wireless and batteryless transmitter, Harmony XB5R, plastic black
Descrizione estesa	This rope pull switch is part of the range Harmony XB5R plastic and XB4R metal wireless and batteryless pushbuttons. It features a rope pull switch with wireless and batteryless transmitter. Its pulling force is from 45N to 1000N. The rope pull switch is adapted for automatic doors. It sends a radio message to the receiver in the control panel to open and close the door. It operates with the protocol Zigbee green power 2.4 GHz in compliance with IEEE 802.15.4. It is impact resistant, dust resistant, water resistant and vibration resistant thanks to its IP66. It weighs 150g.
Completezza BMEcat	98
Codice TARIC	1741
Peso	0 kg