# RIEPILOGO DATI DI CATALOGO

## Telemecanique (Schneider) - RICEVITORE CONFIGURABILE USCITA 4 PNP

| | |
|---|---|
| **Codice prodotto** | SNRZBRRC |
| **Produttore** | Telemecanique (Schneider) |
| **Categoria** | ACCESSORI TELEMECANIQUE (SCHNEIDER) |
| **Codice doganale** | 1741 |

### DESCRIZIONE

This configurable receiver is part of the ranges Harmony XB5R plastic and XB4R metal wireless and batteryless pushbuttons. It is equipped with 2 buttons (teach and parameter setting), 6 indicating LEDs (power ON, function modes, output status, signal strength). It features 4 PNP outputs, 200 mA /24 V and it can be supplied with 24V DC. It is easily combined with wireless and batteryless pushbuttons XB4R/XB5R and limit switches XCKW/XCMW. It operates with the protocol Zigbee green power 2.4 GHz in compliance with IEEE 802.15.4. Its protection index is IP20. It weighs 130g and its dimensions are, 36mm wide, 108mm high, 75mm deep.

### DATI DI CATALOGO

| | |
|---|---|
| **Sigla Metel** | SNR |
| **Codice Metel** | SNRZBRRC |
| **Codice produttore** | ZBRRC |
| **Marca** | Schneider Electric Spa |
| **Stato prodotto** | Stato Metel 3 |
| **Data ultimo aggiornamento** | LS |
| **Data certificazione** | 2026-09-10 |
| **Data variazione** | 2026-10-01 |
| **EAN** | 3606480334719 |
| **Classe ETIM** | EC002024 |
| **Versione ETIM** | 10 |
| **Prezzo pubblico** | 240.50 |
| **Valuta** | EUR |
| **Moltiplicatore prezzo** | 1 |
| **Unita misura** | PCE |

# RIEPILOGO DATI DI CATALOGO

| | |
|---|---|
| **Lead time** | 2 |
| **Quantita minima** | 1 |
| **Quantita multipla** | 1 |
| **Quantita cartone** | 64 |
| **Codice doganale** | Da verificare |
| **Famiglia statistica** | Comando |
| **Codice famiglia statistica** | AUTPEMCESCOM |
| **Keyword** | 6 status led receiver \| Harmony XB5R programmable receiver \| configurable receiver \| remote control station receiver \| 2.4 GHz receiver \| omnidirectional antenna receiver \| ZBRRC receiver \| 24V dc receiver \| zigbee green power receiver \| 4 pnp transistor output receiver \| 1 channel receiver \| 2ms time delay receiver \| ip20 programmable receiver \| 2 pushbutton receiver |
| **Descrizione breve** | Programmable receiver, Harmony XB5R, 4 PNP, 2 buttons, 6 indicating LEDs, monostable, 24V DC |
| **Descrizione estesa** | This configurable receiver is part of the ranges Harmony XB5R plastic and XB4R metal wireless and batteryless pushbuttons. It is equipped with 2 buttons (teach and parameter setting), 6 indicating LEDs (power ON, function modes, output status, signal strength). It features 4 PNP outputs, 200 mA /24 V and it can be supplied with 24V DC. It is easily combined with wireless and batteryless pushbuttons XB4R/XB5R and limit switches XCKW/XCMW. It operates with the protocol Zigbee green power 2.4 GHz in compliance with IEEE 802.15.4. Its protection index is IP20. It weighs 130g and its dimensions are, 36mm wide, 108mm high, 75mm deep. |
| **Completezza BMEcat** | 98 |
| **Codice TARIC** | 1741 |
| **Peso** | 0 kg |