RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TRASFORMATORE 400VAC

Codice prodotto	SNRZBV5B
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony ZB, transformer block is supplied with 400Vac. It is compatible with Harmony XB4 and XB5 light blocks with integral LED. This transformer block is designed to be used with light blocks with integral LED and is compatible with Harmony XB4 and XB5 lighting in control and signaling units. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -25°C to 70°C allows versatility in usage of product. Vibration resistant screw clamp connection terminals ensure high vibration resistance making product suitable installation on high impact machine.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBV5B
Codice produttore	ZBV5B
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389119039789
Classe ETIM	EC000203
Versione ETIM	10
Prezzo pubblico	35.95
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	2
Quantita minima	1
Quantita multipla	1
Quantita cartone	32
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	400v | BA9s base | Clip-together component system | light block | Transmer block | Dust resistant | Screw clamp terminal connections | Harmony XB4 | Harmony XB5 | Impact resistant
Descrizione breve	Transformer block, Harmony XB4, for light block with integral LED, 400V
Descrizione estesa	This Harmony ZB, transformer block is supplied with 400Vac. It is compatible with Harmony XB4 and XB5 light blocks with integral LED. This transformer block is designed to be used with light blocks with integral LED and is compatible with Harmony XB4 and XB5 lighting in control and signaling units. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -25°C to 70°C allows versatility in usage of product. Vibration resistant screw clamp connection terminals ensure high vibration resistance making product suitable installation on high impact machine.
Completezza BMEcat	100
Codice TARIC	1741
Peso	0 kg