RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - TRASFORMATORE 440-460VAC

Codice prodotto	SNRZBV8B
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony ZB, transformer is supplied with 440 to 460Vac. It is compatible with Harmony XB4 light block with integral LED. This transformer block is designed to be used with light blocks with integral LED and is compatible with Harmony XB4 and XB5 lighting in control and signaling units. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -25°C to 70°C allows versatility in usage of product. Vibration resistant screw clamp connection terminals ensure high vibration resistance making product suitable installation on high impact machine.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBV8B
Codice produttore	ZBV8B
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389119039796
Classe ETIM	EC000203
Versione ETIM	10
Prezzo pubblico	38.30
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	2
Quantita minima	1
Quantita multipla	1
Quantita cartone	32
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	collegamento con morsetti a vite | LED integrato | XB5 | resistente alla polvere | Per morsettiera luminosa | Elemento trasformatore | XB4 | Harmony
Descrizione breve	Transformer block, Harmony XB4, for light with integral LED, 24V AC, 440...460V 60Hz
Descrizione estesa	This Harmony ZB, transformer is supplied with 440 to 460Vac. It is compatible with Harmony XB4 light block with integral LED. This transformer block is designed to be used with light blocks with integral LED and is compatible with Harmony XB4 and XB5 lighting in control and signaling units. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -25°C to 70°C allows versatility in usage of product. Vibration resistant screw clamp connection terminals ensure high vibration resistance making product suitable installation on high impact machine.
Completezza BMEcat	100
Codice TARIC	1741
Peso	0 kg