RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - LED BIANCO 24V FASTON

Codice prodotto	SNRZBVB13
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony ZB, white light block operates with a universal LED. It is supplied with 24V AC/DC and uses fast-on terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by universal LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBVB13
Codice produttore	ZBVB13
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110816594
Classe ETIM	EC000204
Versione ETIM	10
Prezzo pubblico	11.46
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE

RIEPILOGO DATI DI CATALOGO

Lead time	B
Quantita minima	5
Quantita multipla	5
Quantita cartone	5
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	universal LED | Dust resistant | Impact resistant | Self-earthing | Modular | Screw clamp terminal connection | faston connector | Schneider Electric | White | Clip-together component system | Light block | XB5 | XB4
Descrizione breve	Head for light block, Harmony XB5, XB4, 22mm, universal LED, faston connector, 24V
Descrizione estesa	This Harmony ZB, white light block operates with a universal LED. It is supplied with 24V AC/DC and uses fast-on terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by universal LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	75
Codice TARIC	1741
Peso	0 kg