RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - ELEMENTO LED LUMINOSO BIANCO

Codice prodotto	SNRZBVB14
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony ZB, white light block operates with a universal LED. It is supplied with 24V AC/DC and uses plug-in terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by universal LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBVB14
Codice produttore	ZBVB14
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110090147
Classe ETIM	EC000204
Versione ETIM	10
Prezzo pubblico	8.75
Valuta	EUR
Moltiplicatore prezzo	1

RIEPILOGO DATI DI CATALOGO

Unita misura	PCE
Lead time	7
Quantita minima	5
Quantita multipla	5
Quantita cartone	200
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	ip20 light block | universal LED light block | steady signaling light block | white light block | 24vac/dc light block | harmony xb4 light block | zbv light block | xb5 light block | lamp holder | lamp holder block | light block for head | harmony xb5 light block | 22mm light block
Descrizione breve	Light block, Harmony XB4, Harmony XB5, for head 22mm, universal LED, plug-in connector, 24V AC DC
Descrizione estesa	This Harmony ZB, white light block operates with a universal LED. It is supplied with 24V AC/DC and uses plug-in terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by universal LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	100
Codice TARIC	1741
Peso	0 kg