RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - ELEMENTO LED LUMINOSO BIANCO

Codice prodotto	SNRZBVG1
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony ZB, XB5 white Light block operates with a universal LED. It is supplied with 110V to 120V AC and uses screw clamp terminals. It has a plastic body. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by universal LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. It features high endurance LED lighting for less replacement and process downtimes. Vibration resistant screw clamp connection terminals ensure high vibration resistance making product suitable installation on high impact machine.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBVG1
Codice produttore	ZBVG1
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110089660
Classe ETIM	EC000204
Versione ETIM	10
Prezzo pubblico	9.47
Valuta	EUR

RIEPILOGO DATI DI CATALOGO

Moltiplicatore prezzo	1
Unita misura	PCE
Lead time	4
Quantita minima	5
Quantita multipla	5
Quantita cartone	800
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Clip-together component systemuniversal LED | Light block | Screw clamp terminal connection | XB4 | Self-earthing | Dust resistant | Harmony XB5 | Impact resistant
Descrizione breve	Light block, Harmony XB4, Harmony XB5, for head 22mm, universal LED, screw clamp terminals, 110...120V AC
Descrizione estesa	This Harmony ZB, XB5 white Light block operates with a universal LED. It is supplied with 110V to 120V AC and uses screw clamp terminals. It has a plastic body. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by universal LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. It features high endurance LED lighting for less replacement and process downtimes. Vibration resistant screw clamp connection terminals ensure high vibration resistance making product suitable installation on high impact machine.
Completezza BMEcat	75
Codice TARIC	1741
Peso	0.009 kg