RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - LED UNIVERSALE 120 VAC - FASTON

Codice prodotto	SNRZBVG13
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	Da verificare

DESCRIZIONE

This Harmony ZB, white light block operates with a universal LED. It is supplied with 110V to 120V AC and uses fast-on terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by universal LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBVG13
Codice produttore	ZBVG13
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110816709
Classe ETIM	EC000204
Versione ETIM	10
Prezzo pubblico	12.13
Valuta	EUR
Moltiplicatore prezzo	1

RIEPILOGO DATI DI CATALOGO

Unita misura	PCE
Lead time	C
Quantita minima	1
Quantita multipla	1
Quantita cartone	1
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	universal LED | faston terminal connector | Schneider Electric | Clip-together component system | White | Self-earthing | Modular | XB4 | XB5 | Impact resistant | Light block | Dust resistant
Descrizione breve	Light block, Harmony XB4, Harmony XB5, for head 22mm, universal LED, faston connector, 110...120V
Descrizione estesa	This Harmony ZB, white light block operates with a universal LED. It is supplied with 110V to 120V AC and uses fast-on terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by universal LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	75
Codice TARIC	Da verificare
Peso	0 kg