RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - LED UNIVERSALE 12VAC/DC FASTON

Codice prodotto	SNRZBVJ13
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	Da verificare

DESCRIZIONE

This Harmony XB4 range is a white light block operates with an integral LED. It is supplied with 12V AC/DC and uses fast-on terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by integral LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBVJ13
Codice produttore	ZBVJ13
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3606482228979
Classe ETIM	EC000204
Versione ETIM	10
Prezzo pubblico	11.74
Valuta	EUR
Moltiplicatore prezzo	1

RIEPILOGO DATI DI CATALOGO

Unita misura	PCE
Lead time	B
Quantita minima	1
Quantita multipla	1
Quantita cartone	5
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	XB5 | Schneider Electric | Modular | Impact resistant | Dust resistant | Harmony | XB4 | Light block | 12v ac/dc | Integral LED | White | Clip-together component system | head 22mm | Faston connections
Descrizione breve	Light block, Harmony XB4, Harmony XB5, 22mm, fast on connection, universal LED, 1NO, 12V AC DC
Descrizione estesa	This Harmony XB4 range is a white light block operates with an integral LED. It is supplied with 12V AC/DC and uses fast-on terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by integral LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	75
Codice TARIC	Da verificare
Peso	0 kg