RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - ELEMENTO LED LUMINOSO BIANCO

Codice prodotto	SNRZBVM14
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony ZB, white light block operates with a universal LED. It is supplied with 230V to 240V AC and uses plug-in terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by universal LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBVM14
Codice produttore	ZBVM14
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110090284
Classe ETIM	EC000204
Versione ETIM	10
Prezzo pubblico	18.73
Valuta	EUR
Moltiplicatore prezzo	1

RIEPILOGO DATI DI CATALOGO

Unita misura	PCE
Lead time	A
Quantita minima	5
Quantita multipla	5
Quantita cartone	80
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Clip-together component systemuniversal LED | 230V to 240V push button | Self-earthingplug-in connection | Impact resistant | Dust resistant | Light block | Harmony XB5 | XB4
Descrizione breve	Light block, Harmony XB4, Harmony XB5, for head 22mm, universal LED, plug in connector, 230...240V
Descrizione estesa	This Harmony ZB, white light block operates with a universal LED. It is supplied with 230V to 240V AC and uses plug-in terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by universal LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	100
Codice TARIC	1741
Peso	0 kg