RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - LED VERDE 230VAC

Codice prodotto	SNRZBVM3M
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	Da verificare

DESCRIZIONE

This Harmony XB4 range is a green light block operates with an integral LED. It is supplied with 110V to 240V AC and uses screw clamp terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by integral LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. It complies with the RoHS directive related to the management of electronic and electrical waste. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZBVM3M
Codice produttore	ZBVM3M
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 6
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3606482228917
Classe ETIM	EC000204
Versione ETIM	10
Prezzo pubblico	21.50
Valuta	EUR
Moltiplicatore prezzo	1

RIEPILOGO DATI DI CATALOGO

Unita misura	PCE
Lead time	B
Quantita minima	5
Quantita multipla	5
Quantita cartone	5
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	Screw clamp terminal connection | Modular | Self-earthing | Impact resistant | Dust resistant | 230 to 240v ac | Integral LED | Green | Clip-together component system | Light block | XB5 | XB4 | Schneider Electric
Descrizione breve	Light block, Harmony XB4, Harmony XB5, green, 22mm, integral LED, 230...240V AC, maintenance
Descrizione estesa	This Harmony XB4 range is a green light block operates with an integral LED. It is supplied with 110V to 240V AC and uses screw clamp terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by integral LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. It complies with the RoHS directive related to the management of electronic and electrical waste. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.
Completezza BMEcat	71.92
Codice TARIC	Da verificare
Peso	0 kg