# RIEPILOGO DATI DI CATALOGO

## Telemecanique (Schneider) - LED ROSSO 230VAC

| | |
|---|---|
| **Codice prodotto** | SNRZBVM4M |
| **Produttore** | Telemecanique (Schneider) |
| **Categoria** | ACCESSORI TELEMECANIQUE (SCHNEIDER) |
| **Codice doganale** | Da verificare |

### DESCRIZIONE

This Harmony XB4 range is a red light block operates with an integral LED. It is supplied with 110V to 240V AC and uses screw clamp terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by integral LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. It complies with the RoHS directive related to the management of electronic and electrical waste. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product.

### DATI DI CATALOGO

| | |
|---|---|
| **Sigla Metel** | SNR |
| **Codice Metel** | SNRZBVM4M |
| **Codice produttore** | ZBVM4M |
| **Marca** | Schneider Electric Spa |
| **Stato prodotto** | Stato Metel 6 |
| **Data ultimo aggiornamento** | LS |
| **Data certificazione** | 2026-09-10 |
| **Data variazione** | 2026-10-01 |
| **EAN** | 3606482228924 |
| **Classe ETIM** | EC000204 |
| **Versione ETIM** | 10 |
| **Prezzo pubblico** | 21.50 |
| **Valuta** | EUR |
| **Moltiplicatore prezzo** | 1 |

# RIEPILOGO DATI DI CATALOGO

| | |
|---|---|
| **Unita misura** | PCE |
| **Lead time** | B |
| **Quantita minima** | 5 |
| **Quantita multipla** | 5 |
| **Quantita cartone** | 5 |
| **Codice doganale** | Da verificare |
| **Famiglia statistica** | Comando |
| **Codice famiglia statistica** | AUTPEMCESCOM |
| **Keyword** | red light block \| steady signaling light block \| integral LED \| zbv light block \| XB5 light block \| lamp holder \| lamp holder block \| light block head \| XB4 light block \| Harmony XB5 \| schneider \| se \| ip20 light block \| 230 to 240vac light block \| 22mm light block, screw clamp terminals \| schneider electric |
| **Descrizione breve** | Light block, Harmony XB4, Harmony XB5, red, 22mm, integral LED, 230...240V AC, maintenance |
| **Descrizione estesa** | This Harmony XB4 range is a red light block operates with an integral LED. It is supplied with 110V to 240V AC and uses screw clamp terminals. It has a plastic body. It is compatible with Harmony XB4 and XB5. This light block allows fast and easy replacement and configuration of your signaling units. It is easily installed and replaced on compatible illuminated push-button or selector switch units via clip together assembly and connected with simple screw-clamp connections. It enables visual distinction of signaling units via illumination by integral LED. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. It complies with the RoHS directive related to the management of electronic and electrical waste. Its wide range of operating temperatures from -40°C to 70°C allows versatility in usage of product. |
| **Completezza BMEcat** | 71.92 |
| **Codice TARIC** | Da verificare |
| **Peso** | 0 kg |