RIEPILOGO DATI DI CATALOGO

Telemecanique (Schneider) - ELEMENTO DI CONTATTO NO

Codice prodotto	SNRZENL1111
Produttore	Telemecanique (Schneider)
Categoria	ACCESSORI TELEMECANIQUE (SCHNEIDER)
Codice doganale	1741

DESCRIZIONE

This Harmony XAL, single contact block uses screw-clamp terminals and has 1 x NO contact. It is compatible with Harmony XB5, 22mm control and signaling units and XAPS control stations. This contact block allows fast and easy replacement and configuration of your pushbuttons and selector switches. It is easily installed and replaced on XB5 complete pushbuttons, selector switches, and XAPS control stations. It connects to control circuits with simple screw-clamp connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance allows less maintenance and damage in your installation. Vibration resistant screw clamp connection terminals ensure high vibration resistance, making product suitable installation on high impact machine.

DATI DI CATALOGO

Sigla Metel	SNR
Codice Metel	SNRZENL1111
Codice produttore	ZENL1111
Marca	Schneider Electric Spa
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-10
Data variazione	2026-10-01
EAN	3389110115079
Classe ETIM	EC000041
Versione ETIM	10
Prezzo pubblico	6.14
Valuta	EUR
Moltiplicatore prezzo	1

RIEPILOGO DATI DI CATALOGO

Unita misura	PCE
Lead time	4
Quantita minima	5
Quantita multipla	5
Quantita cartone	800
Codice doganale	Da verificare
Famiglia statistica	Comando
Codice famiglia statistica	AUTPEMCESCOM
Keyword	22mm Mounting Diameter | NO contact | Screw-Clamp | Rear Mounting | Harmony XAL | ZENL | Contact block
Descrizione breve	Single contact block, Harmony XALD, XALK, silver alloy, rear mounting, screw clamp terminal, 1NO
Descrizione estesa	This Harmony XAL, single contact block uses screw-clamp terminals and has 1 x NO contact. It is compatible with Harmony XB5, 22mm control and signaling units and XAPS control stations. This contact block allows fast and easy replacement and configuration of your pushbuttons and selector switches. It is easily installed and replaced on XB5 complete pushbuttons, selector switches, and XAPS control stations. It connects to control circuits with simple screw-clamp connections. It protects operators from unexpected contact with live circuits thanks to its IP20 protection index. 1 million cycle high endurance allows less maintenance and damage in your installation. Vibration resistant screw clamp connection terminals ensure high vibration resistance, making product suitable installation on high impact machine.
Completezza BMEcat	100
Codice TARIC	1741
Peso	0.0015 kg