RIEPILOGO DATI DI CATALOGO

Alpha Elettronica - Multimetro portatile analogico CAT III 300V | CAT III 300V analog portable multimeter

Codice prodotto	ALP98730
Produttore	Alpha Elettronica
Categoria	Attrezzatura / Strumenti / Multimetri
Codice doganale	Da verificare

DESCRIZIONE

RIEPILOGO DATI DI CATALOGO

Compact and robust analog portable multimeter that combines traditional analog measurement technique with modern equipment. The inputs are protected against overloads. The multimeter has six measurement ranges: Voltage (DC), Current (DC), Voltage (AC), Current (AC), Resistance, Decibel, Battery Test (1.5V and 9V).

General Characteristics
Type of Meter: Analog multimeter
Measurable quantities: AC voltage, DC voltage, Resistance, DC current, Battery test
Detection: Continuità
Indication: Graduated scale
Selectable units of measurement: V, mA
Protections: Sovraccarico
Data Hold: No
Memory: No
PC Interface: No
Updatable Software/Firmware: No
Self-Diagnostic Function: No
Automatic Shutdown: No
Connections: Puntali
Included Accessories: Puntali

Electrical Characteristics
Safety Level: Cat III
Type of Power Supply: Battery
DC Supply Voltage: 1.5Vdc
Battery Type: 1xAAA
Batteries: Not Included

Mechanical Characteristics
Protection Degree: IP20

Caratteristiche Meccaniche
Formato: Tascabile

Mechanical Characteristics
Dimensions: 28mm x 85mm x 119mm
Working Temperature: 0 / 40°C
Storage Temperature: -10 / 50°C
Relative Atmospheric Humidity: <80%

Measurement Characteristics
DC Voltage: 12 - 300Vdc
DC Voltage Measurement Accuracy: FSD 5
AC Voltage: 60 - 300Vac
AC Voltage Measurement Accuracy: FSD 5
DC Current: 30 - 600mA
DC Current Measurement Accuracy: FSD 5
Resistance: 1 - 1MOhm
Resistance Measurement Accuracy: Accuratezza valore centrale 5%
 | Multimetro portatile analogico compatto e robusto che unisce la tecnica di misurazione analogica tradizionale a un equipaggiamento moderno. Gli ingressi sono protetti contro i sovraccarichi. Il multimetro ha sei gamme di misurazione: Tensione (CC), Corrente (CC), Tensione (CA), Corrente (CA), Resistenza, Decibel, Prova batterie (1.5V e 9V).

RIEPILOGO DATI DI CATALOGO

DATI DI CATALOGO

Sigla Metel	ALP
Codice Metel	ALP98730
Codice produttore	98-730
Marca	Alpha Elettronica Srl
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-29
Data variazione	2026-10-01
EAN	8017443550513
Classe ETIM	EC000069
Versione ETIM	8
Prezzo pubblico	26.00
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE
Lead time	4
Quantita minima	1
Quantita multipla	1
Quantita cartone	5
Codice doganale	Da verificare
Famiglia statistica	Attrezzatura / Strumenti / Multimetri
Codice famiglia statistica	947-1289-1475
Keyword	Alpha elettronica | Join | Tester | Multimetro | Elettronica | Multimetri | Strumenti | Alfa | Alpha | Attrezzatura
Descrizione breve	Multimetro portatile analogico CAT III 300V | CAT III 300V analog portable multimeter

RIEPILOGO DATI DI CATALOGO

Descrizione estesa	Compact and robust analog portable multimeter that combines traditional analog measurement technique with modern equipment. The inputs are protected against overloads. The multimeter has six measurement ranges: Voltage (DC), Current (DC), Voltage (AC), Current (AC), Resistance, Decibel, Battery Test (1.5V and 9V). General Characteristics Type of Meter: Analog multimeter Measurable quantities: AC voltage, DC voltage, Resistance, DC current, Battery test Detection: Continuità Indication: Graduated scale Selectable units of measurement: V, mA Protections: Sovraccarico Data Hold: No Memory: No PC Interface: No Updatable Software/Firmware: No Self-Diagnostic Function: No Automatic Shutdown: No Connections: Puntali Included Accessories: Puntali Electrical Characteristics Safety Level: Cat III Type of Power Supply: Battery DC Supply Voltage: 1.5Vdc Battery Type: 1xAAA Batteries: Not Included Mechanical Characteristics Protection Degree: IP20 Caratteristiche Meccaniche Formato: Tascabile Mechanical Characteristics Dimensions: 28mm x 85mm x 119mm Working Temperature: 0 / 40°C Storage Temperature: -10 / 50°C Relative Atmospheric Humidity: <80% Measurement Characteristics DC Voltage: 12 - 300Vdc DC Voltage Measurement Accuracy: FSD 5 AC Voltage: 60 - 300Vac AC Voltage Measurement Accuracy: FSD 5 DC Current: 30 - 600mA DC Current Measurement Accuracy: FSD 5 Resistance: 1 - 1MOhm Resistance Measurement Accuracy: Accuratezza valore centrale 5% | Multimetro portatile analogico compatto e robusto che unisce la tecnica di misurazione analogica tradizionale a un equipaggiamento moderno. Gli ingressi sono protetti contro i sovraccarichi. Il multimetro ha sei gamme di misurazione: Tensione (CC), Corrente (CC), Tensione (CA), Corrente (CA), Resistenza, Decibel, Prova batteria (1,5V e 9V). Caratteristiche Generali Tipo di misuratore: Multimetro analogico Grandezze misurabili: Tensione AC, Tensione DC, Resistenza

RIEPILOGO DATI DI CATALOGO

Completezza BMEcat	59.31