RIEPILOGO DATI DI CATALOGO

Alpha Elettronica - Inverter Onda pura 1500W Ingresso: 24Vdc, Uscita: 230Vac - con bypass 230V | Pure Wave Inverter 1500W Input: 24Vdc, Output: 230Vac - with 230V bypass

Codice prodotto	ALPKX150024
Produttore	Alpha Elettronica
Categoria	Energia / Inverter / Ad isola
Codice doganale	Da verificare

DESCRIZIONE

RIEPILOGO DATI DI CATALOGO

<p>
General Characteristics
Inverter Type: with bypass 230V
Operating Mode: Priorities DC
Cooling: Forced Convection - Automatic fan
Additional features: Energy saving mode, Ignition start port
Control Interface: Tasti fisici, Display remoto opzionale, RJ12

Inverter Features
Waveform Output: Pure sine
Frequency: 50Hz
Wave Distortion Thd: <3%
Max AC input current: 6.5A
Input Current: 70.5A
Input Voltage: 24Vdc
Output Voltage: 230Vac
Output voltage configuration: selezionabile 220-230-240Vac
Output frequency configuration: selezionabile 50-60Hz
Under-voltage protection: 21±0,3Vdc
Peak output power: 3000W
Rated Power Output: 1500W
Maximum Efficiency: 91%
Minimum Battery Capacity: >80Ah
Stand By No-Load Consumption: <0.5A
Bypass relay current: 16A
Bypass relay current load type: resistive
Minimum Operative Load: 20W
Selectable low voltage protection setting: 21/21,6/22,6/23,6Vdc
Soft Start: yes
Transfer Switch: Automatic
Switching Time: 30ms
Protections: Low voltage, Short circuit, Reverse polarity, Overload, Overtemperature, Input overvoltage
Restart function: Overload (manual), Overtemperature (manual), Overvoltage (automatic), High volt battery (automatic)
Fuse: internal
Fuse Features: 3x 40A

Mechanical Characteristics
Dimensions: 331.2mm x 150.1mm x 77.6mm
Weight: 2.6Kg
Protection: IP20
Installation: wall, landscape
Noise level: 64dB

Thermal Features
Working Temperature: -10 / 40°C
Humidity: 5 ÷ 90%

Connections
Remote Controls: optional
Input Cable: Una coppia di cavi rosso-nero 25mm²/3AWG 1m
Input Connections: screw terminals for eyelets, IEC320 C14

RIEPILOGO DATI DI CATALOGO

DATI DI CATALOGO

Sigla Metel	ALP
Codice Metel	ALPKX150024
Codice produttore	KX1500/24
Marca	Alpha Elettronica Srl
Stato prodotto	Stato Metel 3
Data ultimo aggiornamento	LS
Data certificazione	2026-09-29
Data variazione	2026-10-01
EAN	8017443689954
Classe ETIM	EC001747
Versione ETIM	8
Prezzo pubblico	430.00
Valuta	EUR
Moltiplicatore prezzo	1
Unita misura	PCE
Lead time	4
Quantita minima	1
Quantita multipla	1
Quantita cartone	2
Codice doganale	Da verificare
Famiglia statistica	Energia / Inverter / Ad isola
Codice famiglia statistica	941-1304-1698
Keyword	Alpha | Inverter | Join | Energia | Alpha elettronica | Alfa | Elettronica
Descrizione breve	Inverter Onda pura 1500W Ingresso: 24Vdc, Uscita: 230Vac - con bypass 230V | Pure Wave Inverter 1500W Input: 24Vdc, Output: 230Vac - with 230V bypass

RIEPILOGO DATI DI CATALOGO

	  General Characteristics Inverter Type: with bypass 230V Operating Mode: Priorities DC Cooling: Forced Convection - Automatic fan Additional features: Energy saving mode, Ignition start port Control Interface: Tasti fisici, Display remoto opzionale, RJ12 Inverter Features Waveform Output: Pure sine Frequency: 50Hz Wave Distortion Thd: <3% Max AC input current: 6.5A Input Current: 70.5A Input Voltage: 24Vdc Output Voltage: 230Vac Output voltage configuration: selezionabile 220-230-240Vac Output frequency configuration: selezionabile 50-60Hz Under-voltage protection: 21±0,3Vdc Peak output power: 3000W Rated Power Output: 1500W Maximum Efficiency: 91% Minimum Battery Capacity: >80Ah Stand By No-Load Consumption: <0.5A Bypass relay current: 16A Bypass relay current load type: resistive Minimum Operative Load: 20W Selectable low voltage protection setting: 21/21,6/22,6/23,6Vdc Soft Start: yes Transfer Switch: Automatic Switching Time: 30ms Protections: Low voltage, Short circuit, Reverse polarity, Overload, Overtemperature, Input overvoltage Restart function: Overload (manual), Overtemperature (manual), Overvoltage (automatic), High volt battery (automatic) Fuse: internal Fuse Features: 3x 40A Mechanical Characteristics Dimensions: 331.2mm x 150.1mm x 77.6mm Weight: 2.6Kg Protection: IP20 Installation: wall, landscape Noise level: 64dB Thermal Features Working Temperature: -10 / 40°C Humidity: 5 ÷ 90% Connections Remote Control: optional Input Cable: Una coppia di cavi rosso-nero 25mm²/3AWG 1m Input Connections: screw terminals for eyelets, IEC320 C14 Output Connections: 1 USB-A 5V 2,1A socket
Dati prodotto acquisiti dal catalogo Metel One Place	| La serie KX di inverter di potenza a onda sinusoidale pura con Transfer Switch è una combinazione di un inverter e di un interruttore di trasferimento automatico AC che permette di commutare tra lalimentazione proveniente dalla rete elettrica (quando disponibile) e quella fornita dallinverter stesso (quando la

RIEPILOGO DATI DI CATALOGO

Completezza BMEcat	64.97